

High Temperature Panel Filter



About this product

High-quality ceiling filter cassettes in painting and drying systems and units

- **Filter pack AL200 und UG300**

- High temperature ceiling filter cassettes
- High quality fiberglass media
- Temperature resistance:
 - AL200 up to max. 200°C
 - UG300 up to max. 300°C

- **Filter pack SK100 und ZH120**

- High quality ceiling filter cassettes
- Synthetic filter media
- Glass reinforcement scrim on the dirty air side
- Temperature resistance:
 - SK100 up to max. 100°C
 - ZH120 up to max. 120°C

Applications

- Industrial high-temperature ovens for coating or painting
- Hot air high-temp ovens
- General dust filters

Specifications

Type	Filter class <i>ISO 16890 (EN 779)</i>	Width <i>mm</i>	Height <i>mm</i>	Depth <i>mm</i>	Initial pressure drop <i>Pa</i>	Airflow <i>m³/h</i>
Filter pack - AL200	ISO ePM10 50% (M5)	480	480	14	105	500
Filter pack - SK100	ISO ePM10 50% (M5)	480	480	14	150	1000
Filter pack - UG300	ISO Coarse 60% (G4)	480	480	14	55	1000
Filter pack - ZH120	ISO ePM10 50% (M5)	480	480	20	140	1000